

DRILLING ATTACHMENT

# MICRO CPA 360



HOLE DIAMETER  
26-76 mm  
1 - 3"



MAX DEPTH  
3,2 m  
10.5'



CARRIER WEIGHT  
10-14 t  
22,000-30,900 lb

TRANSFORMS AN EXCAVATOR  
INTO A SURFACE DRILL

EQUIPPED WITH MONTABERT HC20 OR HC25

OPTIMIZED AND REDUCED  
OPERATION COSTS

RADIOCONTROL INCLUDED AS STANDARD

DIMENSIONAL STONE CURRING,  
TRENCHING, PRE-SPLITTING,  
BLASTING, GROUND SUPPORT

## BENEFITS

- **Ergonomic attachment:** the perfect drilling tool for lightweight excavators, offering easy installation, excellent versatility and maximum efficiency.
- **Versatility:** with the agility of an excavator, it can be used for drilling in difficult-to-access areas, on uneven terrain and at height. The CPA can also handle complex jobs such as anchoring, bolting and secondary breaking.
- **Economical:** coupled with a quick coupler, the excavator becomes a versatile machine for drilling with a CPA, breaking rock with a rock breaker or digging with a bucket.
- **360° positioning:** the slew drive allows bolting and tie back operations in various construction sites, especially in tunnels.
- **Take it to the next level:** carry out maintenance operations in tunnels, urban construction or any other type of narrow, hard-to-reach worksites, thanks to its compact size.

## DRILLING ATTACHMENT

# LICENSE TO DRILL

WEIGHT AND DIMENSIONS <small>(WITH RODS, WITHOUT ADAPTER PLATE)</small>	METRIC	IMPERIAL
WEIGHT (MIN-MAX)	710 - 840 kg	1,565 - 1,951 lb
LENGTH	4,746 mm	15.6'
WIDTH WITHOUT DUST COLLECTOR	767 mm	2.5'
WIDTH WITH DUST COLLECTOR	1,335 mm	4.4'
HEIGHT WITH DUST COLLECTOR	1,410 mm	4.6'

DRIFTER HC20	METRIC	IMPERIAL
POWER	4 kW	5 hp
STRIKE FREQUENCY (MAX)	2,820 BPM	48 Hz
TORQUE (MAX)	401 Nm	296 ft. lb
FLUSHING	Air	
REVERSE PERCUSSION	Mechanical	

DRIFTER HC25	METRIC	IMPERIAL
POWER	8 kW	11 hp
STRIKE FREQUENCY (MAX)	3,900 BPM	65 Hz
TORQUE (MAX)	401 Nm	296 ft. lb
FLUSHING	Air	
REVERSE PERCUSSION	Mechanical	

OPERATING INFORMATION	METRIC	IMPERIAL
CARRIER WEIGHT (MIN-MAX)	10 - 14 t	22,046 - 30,865 lb
OIL FLOW - HC20 (MIN-MAX)	60 - 75 l/min	16 - 20 GPM
OIL FLOW - HC25 (MIN-MAX)	80 - 95 l/min	20 - 25 GPM
WORKING PRESSURE	165 bar	2,392 PSI
FLUSHING AIR FLOW (WITHOUT DUST COLLECTOR)	2.0 m <sup>3</sup> /min	71 CFM
FLUSHING AIR FLOW (WITH DUST COLLECTOR)	3.7 m <sup>3</sup> /min	131 CFM
ELECTRICAL SUPPLY	12 V / 24 V DC	

MAST CAPACITY	METRIC	IMPERIAL
SHANKS	H22 / H25 / R25 / R32	
ROD LENGTH	3,660 mm	12'
DRILLED LENGTH	3,200 mm	10.5'
DRILLING DIAMETER (MIN-MAX)	26 - 76 mm	1 - 3"
TILT	+/- 180°	




## FEATURES

- RADIOCONTROL
- EMERGENCY STOP
- ANTI-JAMMING
- INTEGRATED AIR LUBRICATOR (GM44)
- CHAIN FEED SYSTEM
- HOSE CARRIER

## OPTIONS

- DUST COLLECTOR
- MECHANICAL / HYDRAULIC ROD CENTRALIZER
- HYDRAULIC SHANK RETAINER
- 2D ANGLE INDICATOR



The content of this brochure constitutes non-binding information and may be changed at any time without notice. Montabert gives, and the brochure contains, no warranties whatsoever, express or implied. All the contents, including but not limited to text, images, graphics are all subject to copyright and all intellectual property protection. Their use or misuse is strictly prohibited. Montabert brand and logo used herein are the property of Montabert. Nothing contained on this document shall be construed as constituting any commitment by Montabert or as granting any license or right to use any intellectual property.

©2024 Montabert. All rights reserved.

[tramac.com](http://tramac.com) - [montabert.com](http://montabert.com)

